

# Autowave Guncleaner

FOR PROFESSIONAL USE ONLY

## Description

Special cleaning agent suitable for cleaning and rinsing of equipment used for the application of waterborne products equipment.

### Use suitable respiratory protection



AkzoNobel Car Refinishes recommends providing adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn. Use safety eyewear designed to protect against splash of liquids.

Besides respiratory protection, always wear solvent resistant gloves while cleaning or degreasing even if working with a low solvent degreaser. This will reduce the risk of cleaning solvents being absorbed into the skin and prevent salts and oils on your hands from contaminating the surface to be refinished.

Read complete TDS for detailed product information

## Cleaning process

After use equipment should be cleaned immediately by thoroughly rinsing all deposits away until material runs clear. Subsequently rinse with a little amount of Activator WB.

### Automatic gun cleaning:

For the most efficient automatic gun cleaning, the machine should be filled with pure Autowave Guncleaner.

### Manual gun cleaning:

Autowave Guncleaner is ready to use for cleaning purpose.

If a water borne product is allowed to dry, clean the equipment with a suitable Solvent before cleaning as specified above.

*Do not allow aluminum equipment to soak immersed in Autowave Guncleaner. It is advised to select a gun specifically designed and solely to use with water borne products.*

## Product and additives

- Autowave Guncleaner
- Autowave Separator

## Basic raw materials

Water and solvents

## VOC

The VOC content of this product in ready to use form is max. 96 g/liter

## Product storage

Product shelf-life is determined when products are stored unopened at 70°F (20°C).

Avoid too much temperature fluctuation.

- o For optimum performance, store opened products at application temperature
- o Maximum transport and storage temperatures between 36.5°F-95°F (2 ½ °C-35°C).

Product shelf life 4 years at 70°F





North America

Technical Data Sheet 6.71

Thinner  
05.11.2010

# Autowave Guncleaner

FOR PROFESSIONAL USE ONLY

**Akzo Nobel Car Refinishes Inc. North America**

**Address: 5555 Spalding Drive, Norcross. GA 30092 USA**

**Tel: 770-662-8464**

## FOR PROFESSIONAL USE ONLY

**IMPORTANT NOTE** The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advices given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Coatings brand names mentioned in this data sheet are trademarks of or are licensed to AkzoNobel.

### Head Office

Akzo Nobel Car Refinishes B.V., PO Box 3 2170 BA Sassenheim, The Netherlands. [www.sikkenscr.com](http://www.sikkenscr.com)

