


Separator WB

FOR PROFESSIONAL USE ONLY

Description

Powder to separate paint particles from contaminated Guncleaner WB.



Ready For Use

**Use suitable respiratory protection**

AkzoNobel Car Refinishes recommends the use of a fresh air supply respirator

Read complete TDS for detailed product information

Product and additives

Separator WB
Can be used in contaminated Guncleaner WB

Basic raw materials

Silicates and polymers

Application process

Guncleaner WB can be reclaimed by adding 1% by weight (10 grams/ltr or 37.5 grams/gal) of Separator WB to the contaminated Guncleaner WB. If necessary, add another ½-1% of Separator WB to coagulate the remaining contamination. All existing coagulation devices work according to the same process:


1. Add the Separator WB as specified to the contaminated Guncleaner WB.
2. Stir/mix thoroughly until paint particles have been coagulated.
3. Pour mixture through fine filter bag in order to separate solids from liquid.
4. The Guncleaner WB can now be used again

Guncleaner WB can effectively be recycled three times, after which, it should be disposed of.

Product storage

Product shelf-life is determined when products are stored unopened at 20°C.
Separator WB must be stored in closed can to avoid any contact with water/moisture dampness.
After contact with water/moisture product will have limited shelf life.
Avoid extreme temperature fluctuation.

Product shelf life 4 years at 70°F (20°C)





North America

Technical Data Sheet L5.02.01
Special Products
04.21.2010

Separator WB

FOR PROFESSIONAL USE ONLY

Akzo Nobel Car Refinishes Inc. North America

Address: 5555 Spalding Drive, Norcross. GA 30092 USA

Tel: 770-662-8464

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advices given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Coatings brand names mentioned in this data sheet are trademarks of or are licensed to AkzoNobel.

Head Office

Akzo Nobel Car Refinishes B.V., PO Box 3 2170 BA Sassenheim, The Netherlands. www.lesonalcr.com

