




WANDA DEGREASER

408.10400

FOR PROFESSIONAL USE ONLY

Description

Wanda Degreaser is designed to remove dirt, oils, grease, dust and other contaminants that prevent proper topcoat adhesion and optimal final appearance.



Mixing Ratio:

Ready to Use



Use suitable respiratory protection

Akzo Nobel Car Refinishes Inc. recommends the use of a fresh air supply respirator

Read complete TDS for detailed product information



WANDA DEGREASER

408.10400

FOR PROFESSIONAL USE ONLY

Description

Wanda Degreaser is designed to remove dirt, oils, grease, dust and other contaminants that prevent proper topcoat adhesion and optimal final appearance.


Products and additives

Product: Wanda Degreaser - 408.10400

Basic raw materials

Wanda Degreaser: Aromatic solvents

Material preparation and mixing



Ready to use

Application process



Wash surface with warm water and soap. Rinse with clean water and dry with a clean cloth. Apply ready to use Wanda Degreaser to a clean dry cloth and wipe on the panel. This will remove surface contaminants and prepare for optimal adhesion of the paint system. Concentrate on 12 by 12 inch areas. Wipe off the degreaser with a clean, dry towel, turning the towel often. Repeat this process until the entire panel is clean.

Note: Degreaser can be used on metal or plastic substrates, primers and old refinishes after sanding. Do not leave the surface exposed for an extended time after degreaser is applied. If this occurs, repeat the cleaning and degreasing process for the affected area.

VOC

The VOC content of this product is 6.25 lb/gal. (749 g/L)

Storage

Product shelf-life is determined when products are stored unopened.
Shelf life: 3 years at 60°F and 95°F (15°C and 35°C), no humidity

Notes

- Use proper Personal Protection Equipment, refer to MSDS for Health and Safety Data
- Regularly replace cloths used for degreasing and cleaning with clean ones. Always place used degreasing rags in a sealed container that meets local requirements to avoid the risk of a spontaneous combustion fire.

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE: The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advices given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Coatings brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Head Office

Akzo Nobel Car Refinishes Inc. 5555 Spalding Drive Norcross, GA 30092, USA.