

## R859 Wax & Grease Remover

### FOR PROFESSIONAL USE ONLY

Description
-------------

R859 Wax and Grease Remover is solvents especially formulated to remove grease and other contaminants from bare metal, existing finishes, etc.



Water

Wash down the vehicle with detergent and warm water. This will dissolve water-soluble contaminants. i.e., bird droppings, flies, tree sap, etc.



U-Tech R859 Wax and Grease Remover

Wash down area to be repaired with R859 Wax and Greaser Remover. This will remove any contaminant that cannot be removed with water.



With a clean towel, dry off the degreaser and cleaner before it has time to evaporate.  
—Always use one fresh towel for washing down and one fresh dry towel for wiping dry.  
—Replace towels regularly.



### Use suitable respiratory protection

Akzo Nobel Car Refinishes recommends the use of a fresh air supply respirator

Read complete TDS for detailed product information

## R859 Wax & Grease Remover

### FOR PROFESSIONAL USE ONLY

#### Description

R859 Wax and Grease Remover is solvents especially formulated to remove grease and other contaminants from bare metal, existing finishes, etc.

#### Product and additives

Product R859 Wax and Grease Remover


#### Basic raw materials

R859 Wax and Grease Remover: Special Formulated Solvents



#### Suitable Applications

R859 Wax and Grease Remover is a very good general purpose cleaner. It is suitable for cleaning and degreasing bare metal, existing finishes, primer surfacers, etc

#### Application

1.  Water  
Wash down the vehicle with detergent and warm water. This will dissolve water-soluble contaminants. i.e., bird droppings, flies, tree sap, etc.

---

2.  U-Tech R859 Wax and Grease Remover  
Wash down area to be repaired with R859 Wax and Greaser Remover. This will remove any contaminant that cannot be removed with water.
3.   
With a clean towel, dry off the degreaser and cleaner before it has time to evaporate.  
—Always use one fresh towel for washing down and one fresh dry towel for wiping dry.  
—Replace towels regularly.

**NOTE 1:** Always wear gloves when degreasing. This will accomplish two things:  
a) Reduce the risk of solvent being absorbed into your hands.  
b) Prevent salts and oils on your hands from contaminating the surface to be refinished

**NOTE 2:** Replace cloths being used for degreasing and cleaning regularly by clean ones

**NOTE 3:** Always place used degreasing rags in a sealed container that meets local requirements to avoid the risk of spontaneous combustion fire

**NOTE 4:** Never allow the surface cleaner to evaporate, the contaminate will remain. Wipe the surface dry with a clean towel before the degreaser is allowed to evaporate.

**NOTE 5:** Having sanded the existing finish, repeat Steps 2 and 3 one more time after sanding and prior to topcoating.



## R859 Wax & Grease Remover

### FOR PROFESSIONAL USE ONLY

#### VOC

R859 Wax and Grease Remover

7.5 lb/gal

901 g/liter

#### Product storage

Store products unopened, and used products with closed lids preferably between 60°F-95°F (10°C-35°C)  
Avoid too much temperature fluctuation, optimal storage temperature approximately 70°F (20°C)

- R859 Wax and Grease Remover : 2 years

#### FOR PROFESSIONAL USE ONLY

**IMPORTANT NOTE:** The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advices given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Coating brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

#### Head Office

Akzo Nobel Car Refinishes Inc. 5555 Spalding Drive Norcross, GA 30092, USA. [www.akzonobelcarrefinishes.net](http://www.akzonobelcarrefinishes.net)